



V-SIGN INDUSTRIAL CORP., LTD

Add. #26-288 Henghua Tech.park Wuxi city 214000 Jiangsu pr. China
 Tel: 0086-510-82811159 Fax: 0086-510-80235786 Mobile: 0086-150 506 85919
 URL: www.v-signindustrial.com E-MAIL: chorry@v-signmetals.com

HIGH SPEED PVC (SOFT) DOOR

COLD ROOM Door

Standard Configuration

Item	Unit	Standard settings	Remarks
HS special motor	set	0.75KW/1.5KW/2.2KW/220V self-heating motor, IP 56 control panel.	CE Servo motor
Soft curtain	set	High quality cold resistant 3-layers PVC with PU foam 3mm thick, 0.3mm double layers cold resistant mesh cloth middle insulation layer, 2 layers of insulation cotton or aluminum foil reflective film overall 15mm, curtain is heated to prevent frosting, special seals PVC materials both sides,anti-wind 6grade	RAL CODE
Door frame	pair	S/S 304 frame, alloy-aluminum guides, powder painted	White door body
Working temperature		-1 °C to -28 °C	
Control system & accessories		Special Servo motor at cold temperature, DSP chip & encoders, IP56 LED control panel	standard
Photocell or infrared safety protection	set	Both sides photocell safety device protection or top radar sensors, loop motion detectors	standard
Radar or geomagnetic	set	To help opening and closing “ either-or ”	Option
Remote	pc	Telecontrol	Option
Scanning panel	pc	No touch scanning panel to open	Option
Pull switch	pc	Manual switch	Option
Safety edge	set	To protect objects at the bottom when door going down	Option
Switch mode	set	Manual buttons	standard
Opening Speed		0.8-1.5m/s	adjustment
Closing speed		Above 0.6m/s	adjustment
Max.size		Max.width 6m x height 6m	

