



V-SIGN INDUSTRIAL CORP., LTD

Add. #26-288 Henghua Tech.park Wuxi city 214000 Jiangsu pr. China
Tel: 0086-510-82811159 Fax: 0086-510-80235786 Mobile: 0086-150 506 85919
URL: www.v-signmetals.com E-MAIL: chorry@v-signmetals.com

High Speed PVC Cold-room Door

Standard Configuration

Item	Unit	Standard settings	Remarks
HS special motor	set	0.75/1.5KW/2.2KW/220V/50HZ+IP56 control panel	CE servo motor
Soft curtain	set	High strength Material: PU high cold resistant 3-layer PVC cord, with PU foam 3mm thickness, The thickness of 0.3mm double layer cold resistant mesh cloth middle insulation layer, 2 layers of insulation cotton or aluminum foil reflective film overall 15mm, The door curtain is heated to prevent frosting ,special seals PVC materials both sides,anti-wind 6grade	RAL CODE
Door frame	pair	S/S 304 Top frames, aluminum tracks.	White door body
Working temperature		-1 °C to -28 °C	
Control system & accessories		Special Servo motor at cold temperature, DSP chip & encoders, IP56 LED control box	standard
Photoelectric or infrared safety protection	set	Double sides photo-electric safety device protection or top radar reaction. door stop going down to go upside.	standard
Radar or geomagnetic	set	To help opening and closing “ either-or ”	Option
Remote	pc	Telecontrol	Option
Scanning card	pc	No touch scanning button	Option
Pull switch	pc	Manual switch	Option
Safety bottom	set	To protect objects at the bottom when door going down	Option
Switch mode	set	Manual buttons	standard
Opening Speed		0.8-1.5m/s	adjustment
Closing speed		Above 0.6m/s	adjustment
Max.size		Max.width 6m x height 6m	